

Open Hinge Flat Top Base Flight (No-Cling)

Available Flight Height		Available Materials
in	mm	
4.0	102	Polypropylene, Polyethylene, Acetal



Note: Minimum indent is 1.0 in (25.4 mm)

Note: Flights can be cut down to any height required for a particular application.

Note: Each flight rises out of the center of its supporting module, molded as an integral part. No fasteners are required.

Note: The no-cling vertical ribs are on both sides of the flight.

Mesh Nub Top™ Base Flight (No-Cling)

Available Flight Height		Available Materials
in	mm	
4.0	102	Acetal, Polyethylene



Note: Minimum indent is 1.0 in (25.4 mm)

Note: Flights can be cut down to any height required for a particular application.

Note: Each flight rises out of the center of its supporting module, molded as an integral part. No fasteners are required.

Note: The no-cling vertical ribs are on both sides of the flight.

Sideguards

Available Sizes		Available Materials
in	mm	
2	51	Polypropylene
3	76	



Note: The minimum indent is 0.7 in (18mm)

Note: The normal gap between the sideguards and the edge of a flight is 0.3 in (7.6 mm).

Note: When going around the 6 and 10 tooth sprocket, the sideguards will fan out, opening a gap at the top of the sideguard which may allow small products to fall out. The sideguards stay completely closed when going around the 12, 16, and 20 tooth sprockets.

Note: Standard sideguard orientation is angled inward toward the product. If needed, sideguards can be angled outward toward the conveyor.