



Acetal Sprocket^a

No. of Teeth (Chordal Action)	Nom. Pitch Dia. in	Nom. Pitch Dia. mm	Nom. Outer Dia. in	Nom. Outer Dia. mm	Nom. Hub Width in	Nom. Hub Width mm	Available Bore Sizes			
							U.S. Sizes		Metric Sizes	
							Round in	Square in	Round mm	Square mm
13 (2.97%)	6.2	157	6.4	163	1.2	30.5	1-7/16 2	1.5 2.5	40 60	

a. Contact Customer Service for lead times.

Support Wheel

Available Pitch Diameter		Available Bore Sizes			
in	mm	U.S. Sizes		Metric Sizes	
		Round in	Square in	Round mm	Square mm
6.3	160	1-7/16 2	1.5 2.5		40 60

Overlapping Sideguards

Available Height		Available Materials
in	mm	
0.50	12.7	Acetal
1.0	25.4	Acetal

Note: Maximizes product carrying capacity: they fit into the very edge of the belt, with no indent.
Note: Assembly does not require “finger cuts” on the modules, so the belt’s beam strength is uncompromised.
Note: Turn ratio for 0.50 in (12.7 mm) Overlapping Sideguards is 1.6.
Note: Makes the belt’s outer edge more snag-resistant.
Note: Keeps small products from falling through belt gaps.