



Enduralox Polypropylene Composite Split Sprocket^{ab}

| No. of Teeth (Chordal Action) | Nom. Pitch Dia. in | Nom. Pitch Dia. mm | Nom. Outer Dia. in | Nom. Outer Dia. mm | Nom. Hub Width in | Nom. Hub Width mm | Available Bore Sizes | | | |
|-------------------------------|--------------------|--------------------|--------------------|--------------------|-------------------|-------------------|--------------------------------------|------------------|------------------------------------|-----------|
| | | | | | | | U.S. Sizes | | Metric Sizes | |
| | | | | | | | Round in | Square in | Round mm | Square mm |
| 10 (4.89%) | 6.5 | 165 | 6.7 | 170 | 1.5 | 38 | 1.5 2.5 | | 40 60 | |
| 12 (3.41%) | 7.8 | 198 | 8 | 203 | 1.5 | 38 | 1.5 2.5 | | 40 60 | |
| 16 (1.92%) | 10.3 | 262 | 10.5 | 267 | 1.5 | 38 | 2.5 ^c 3.5 ^c | 2.5 ^c | 60 ^c 90 ^c | |



- 1 - Pitch diameter
- 2 - Outer diameter
- 3 - Hub width

a. Contact Customer Service for lead times.
 b. Hardware made from 316 Stainless Steel
 c. Bores are over-sized

Glass Filled Nylon Split Sprocket^a

| No. of Teeth (Chordal Action) | Nom. Pitch Dia. in | Nom. Pitch Dia. mm | Nom. Outer Dia. in | Nom. Outer Dia. mm | Nom. Hub Width in | Nom. Hub Width mm | Available Bore Sizes | | | |
|-------------------------------|--------------------|--------------------|--------------------|--------------------|-------------------|-------------------|--------------------------------|-----------|-----------------------------|-----------|
| | | | | | | | U.S. Sizes | | Metric Sizes | |
| | | | | | | | Round in | Square in | Round mm | Square mm |
| 10 (4.89%) | 6.5 | 165 | 6.7 | 170 | 1.45 | 37 | 1.5 ^b 2.5 | | 40 ^b 60 | |
| 12 (3.41%) | 7.8 | 198 | 8 | 203 | 1.45 | 37 | 1.5 ^b 2.5 3.5 | | 40 ^b 60 90 | |
| 16 (1.92%) | 10.3 | 262 | 10.5 | 267 | 1.45 | 37 | 2.5 3.5 | | 60 90 | |



a. Contact Customer Service for lead times.
 b. 1.5 in and 40 mm bores have a hub width of 1.95 in (50 mm).